

2520

HYDRAMAXX



PORT INDUSTRIES

802 Industrial Dr. | Palmyra, MO 63461

Phone: (573)769-3338 | Fax: (573)769-4026

www.portindustries.com

PORT INDUSTRIES

HYDRAMAXX

2520

GENERAL

TOTAL OVERALL WEIGHT	46,500 LB
HEIGHT	11' 5"
WIDTH	TIRES 11' OVERALL 11' 4"
LENGTH	44'
TRAVEL SPEEDS	TRAVEL SPEEDS
1st Low / High	0 - 2 MPH / 0 - 4 MPH
2nd Low / High	0 - 7.5 MPH / 0 - 15 MPH

TRACTOR UNIT

GROUND CLEARANCE	TRANSMISSION - 27"
WHEEL BASE	12' 10"
FRONT AXLE	OUTBOARD PLANETARY LIMITED SLIP
REAR AXLE	INBOARD PLANETARY w/ HYD. DIFF LOCK
TIRES - STANDARD	800/50R42 LSW, SUPER TRACTION RADIAL
TRACK WIDTH - CENTER LINE OF TIRES	92"
TRANSMISSION	FOUR SPEEDS WITH TWO SPEED SHIFT ON THE GO
AUTO / MANUAL LEVELING	8° RIGHT AND 8° LEFT
AUTO LOAD CONTROL	ADJUSTABLE SET POINT
CAB	HEATING AND AIR CONDITIONING
HYDRAULIC DIFFERENTIAL LOCK	REAR AXLE - HYD. APPLIED
BRAKES	INDEPENDENT INBOARD REAR AXLE - HYD. APPLIED

ENGINE

MAKE & MODEL	CUMMINS QSG12 / TIER IVF
GROSS HORSEPOWER	430 HP @ 2100 RPM'S w/ POWER BULGE (473 HP)
DISPLACEMENT	11.8 LITER / 720 CU. IN
FUEL TANK CAPACITY	150 GALLONS
ELECTRICAL SYSTEM	24 VOLT (12V ACCESSORY)
BATTERIES - (2) 8D-MHD	2800 CCA RC 900
COLD STARTING AID	AIR INTAKE GRID HEATER

DIGGING CHAIN

DIGGING CHAIN	100 MM PITCH EXTENDED PIN/BUSHING
DIGGING CUTTERS	DIRECT MOUNT ON CHAIN
DIGGING DEPTH RANGE	1 - 7' UP TO 11'
DIGGING WIDTH RANGE	11.5 - 28"
STANDARD CUTTING ARRANGEMENT	FULL SET OF 180/290/11.5" WIDE
BOOT WITH PIVOT	3 - 15" SINGLE WALL PIPE

HYDRAULIC SYSTEM

SYSTEM CAPACITY	160 GALLON
OIL TYPE	TH FLUID
FILTRATION	25 MICRON RETURNS / 5 MICRON PRESSURE
HYDRAULIC OIL COOLER	TEMPERATURE CONTROL FAN / OPTIONAL