

HYDRAMAXX

2600



PORT INDUSTRIES

802 Industrial Dr. | Palmyra, MO 63461
Phone: (573)769-3338 | Fax: (573)769-4026
www.portindustries.com

PORT INDUSTRIES

HYDRAMAXX

2600

GENERAL

TOTAL OVERALL WEIGHT	46,000 lbs
HEIGHT	11' 8"
WIDTH	TIRES 10' 6" OVERALL 11' 3"
LENGTH	42' 6"
TRAVEL SPEEDS	TRAVEL SPEEDS
1st Low / High	0 - 2 MPH / 0 - 4 MPH
2nd Low / High	0 - 7.5 MPH / 0 - 15 MPH

TRACTOR UNIT

GROUND CLEARANCE	TRANSMISSION - 27" UPRIGHTS - 19"
WHEEL BASE	12' 6"
FRONT AXLE	OUTBOARD PLANETARY LIMITED SLIP
REAR AXLE	INBOARD PLANETARY w/ HYD. DIFF LOCK
TIRES - STANDARD	30.5 x 32L - 14 PLY SPADE GRIP (R2) TREAD
TRACK WIDTH - CENTER LINE OF TIRES	92"
TRANSMISSION	FOUR SPEED WITH TWO SPEED SHIFT ON THE GO
AUTO/MANUAL LEVELING	8° RIGHT AND 8° LEFT
AUTO LOAD CONTROL (standard)	ADJUSTABLE SET POINT
CAB (standard)	HEAT AND AIR CONDITIONING
HYDRAULIC DIFFERENTIAL LOCK	REAR AXLE - HYD. APPLIED
BRAKES	INDEPENDENT INBOARD REAR AXLE - HYD. APPLIED

ENGINE

MAKE & MODEL	CUMMINS QSM11 / IN LINE 6 CYL. / TIER III COMPLIANT
GROSS HORSEPOWER	350 HP @ 2100 RPM's w/ POWER BULGE (380 HP)
DISPLACEMENT	11 LITER / 693 CU. IN.
FUEL TANK CAPACITY	225 GALLON
ELECTRICAL SYSTEM	24 VOLT
BATTERIES - (2) 8D-MHD	2800 CCA RC 450
COLD STARTING AID	AIR INTAKE GRID HEATER

DIGGING WHEEL

DIGGING WHEEL DIAMETER	97 " INSIDE / 126" OUTSIDE
DIGGING WHEEL CONSTRUCTION	3/4" x 6" RIMS WITH 1/2" x 3" ATTACHING RING
DIGGING DEPTH RANGE	0 - 7' 3"
DIGGING WIDTH RANGE	18" - 32"
STANDARD CUTTING ARRANGEMENT	16" BUCKETS w/ CENTER CUTTERS (22" cut)
SLOPER KIT	OPTIONAL
FRONT CENTER PIVOT	7° RIGHT AND 7° LEFT
GROUND CLEARANCE FOR TRANSPORT	UPRIGHTS - 17" BUCKETS - 36"
PIPE BOX	HYD. BLINDERS 3" - 12" TILE LAYER

CONVEYOR

LENGTH - 8' (STANDARD) 10' (OPTIONAL)
WIDTH - 36"
LEFT OR RIGHT DISCHARGE W/ 36" SHIFT

HYDRAULIC SYSTEM

120 GAL CAPACITY
CITGO TH FLUID OR EQUIVALENT
PRESSURE FILTRATION