

HYDRAMAXX

3310



PORT INDUSTRIES
802 Industrial Dr. | Palmyra, MO 63461
Phone: (573)769-3338 | Fax: (573)769-4026
www.portindustries.com

PORT INDUSTRIES

HYDRAMAXX

3310

GENERAL

TOTAL OVERALL WEIGHT	67-72,000 LB
HEIGHT	11' 11"
WIDTH	11' (11'6" WITH OPTIONAL 36" TRACK PADS)
LENGTH	35'
TRAVEL SPEEDS - LOW/HIGH	0 - 1.8 MPH / 0 - 4.0 MPH
WORKING	AUTOMATIC OPTIMUM SHIFT
GROUND CLEARANCE	18 IN.

TRACTOR AND CONTROLS

XL CAB/ ROPS DESIGN	TINTED WINDOWS
ERGONOMICS CONTROL	AIR RIDE SEAT
RADIO	PLUS 1 MONITOR
STEERING	DOUBLE JOYSTICKS (SINGLE JOYSTICK OPTION)
AUTO / MANUAL LEVELING	8 RIGHT AND 8 LEFT

PLOW

PLOW CONFIGURATION	DOUBLE LINK (CANTILEVER OPTION)
PLOWING DEPTH	0 - 7'
STANDARD PLOW WIDTH FOR 6" PIPE	10 1/4" REPLACEABLE BLADE W/ REPLACEABLE POINT
ADJUSTABLE PLOW SHANK	6" INCREMENTS - 24" TOTAL MOVEMENT
PIPE BOX W/ FLOAT AND PIVOT	3" - 6" STANDARD
POWER FEEDER - STANDARD	3" - 6"
SLOPE METER	STANDARD
PLOW PIVOT STANDARD	HYDRAULIC W/ FLOAT

ENGINE

MAKE & MODEL	CUMMINS QSM11 / IN LINE 6 CYL. / TIER III COMPLIANT
GROSS HORSEPOWER	375 HP
DISPLACEMENT	11 LITER
FUEL TANK CAPACITY	150 GALLON
ELECTRICAL SYSTEM	24V /12 V ACCESSORY
BATTERIES - (2) 8D-MHD	2800 CCA RC 900
COOLING	REVERSIBLE FAN/ETHER AUTO INJECTION

TRACKS

TRACKS LENGTH ON THE GROUND	16.5'
TRACK PAD WIDTH	31.5" (800 mm) (OPTION 36")
D6 UNDERCARRIAGE	SEALED AND LUBRICATED TRACK CHAIN AND ROLLERS
STANDARD TRACK PAD CONFIGURATION	TRIPLE BAR / SINGLE BAR WITH WELDED GROUSER
TRACK DRIVE MOTORS	VARIABLE SPEED DRIVE
LIQUID SPRING TENSIONER I	INCREASED LOAD CAPACITY & RESPONSIVENESS

HYDRAULIC SYSTEM

SYSTEM CAPACITY	70 GALLON
OIL TYPE	CITGO TH FLUID OR EQUIVALENT
FILTRATION	25 MICRON RETURN /5 MICRON PRESSURE