

# HYDRAMAXX

3  
6  
1  
0



**PORT INDUSTRIES**  
802 Industrial Dr. | Palmyra, MO 63461  
Phone: (573)769-3338 | Fax: (573)769-4026  
[www.portindustries.com](http://www.portindustries.com)

# PORT INDUSTRIES

# HYDRAMAXX

# 3610

## GENERAL

TOTAL OVERALL WEIGHT	82,000 LB
HEIGHT	12'
WIDTH	11'
LENGTH	33'
TRAVEL SPEEDS - LOW / HIGH	0 - 2.5 MPH / 0 - 3.5 MPH

## TRACTOR AND PLOW

GROUND CLEARANCE	18 IN.
AUTO / MANUAL LEVELING	8° RIGHT AND 8° LEFT
CAB w/HEAT (STANDARD)	AIR CONDITIONING
STEERING	DOUBLE JOYSTICK (SINGLE JOYSTICK OPTION)
PLOW CONFIGURATION	DOUBLE LINK (CANTILEVER OPTION)
PLOWING DEPTH	0 - 7'
STANDARD PLOW WIDTH	9 1/4" REPLACEABLE BLADE W/ REPLACEABLE POINT
ADJUSTABLE PLOW SHANK	6" INCREMENTS - 24" TOTAL MOVEMENT
PIPE BOX W/ FLOAT AND PIVOT	3" - 6" STANDARD
POWER FEEDER - STANDARD	3" - 6"
SLOPE METER	STANDARD
PLOW PIVOT STANDARD	HYDRAULIC W/ FLOAT

## ENGINE

MAKE & MODEL	DEERE 13.5L / IN LINE 6 CYL. / TIER III COMPLIANT
GROSS HORSEPOWER	550 HP
DISPLACEMENT	13.5 LITER
FUEL TANK CAPACITY	200 GALLON
ELECTRICAL SYSTEM	24/12 VOLT
BATTERIES - (2) 8D-MHD	2800 CCA RC 900

## TRACKS

TRACKS LENGTH ON THE GROUND	17.5'
TRACK PAD WIDTH	31.5" (800 mm)
D7 UNDERCARRIAGE	SEALED AND LUBRICATED TRACK CHAIN AND ROLLERS
STANDARD TRACK PAD CONFIGURATION	TRIPLE BAR / SINGLE BAR WITH WELDED GROUSER
TRACK DRIVE MOTORS	TWO SPEED SHIFT ON THE GO

## HYDRAULIC SYSTEM

SYSTEM CAPACITY	80 GALLON
OIL TYPE	CITGO TH FLUID OR EQUIVALENT
FILTRATION	25 MICRON RETURN / 5 MICRON PRESSURE