

2620

HYDRAMAXX



PORT INDUSTRIES

802 Industrial Dr. | Palmyra, MO 63461
Phone: (573)769-3338 | Fax: (573)769-4026
www.portindustries.com

PORT INDUSTRIES

HYDRAMAXX

2620

GENERAL

TOTAL OVERALL WEIGHT	50,000 lbs
HEIGHT	11' 8"
WIDTH	TIRES 11' OVERALL 11' 4"
LENGTH	43' 5"
TRAVEL SPEEDS	TRAVEL SPEEDS
1st Low / High	0 - 2 MPH / 0 - 4 MPH
2nd Low / High	0 - 7.5 MPH / 0 - 15 MPH

TRACTOR UNIT

GROUND CLEARANCE	TRANSMISSION - 27" UPRIGHTS - 17"
WHEEL BASE	12' 10"
FRONT AXLE	OUTBOARD PLANETARY LIMITED SLIP
REAR AXLE	INBOARD PLANETARY w/ HYD. DIFF LOCK
TIRES - STANDARD	800 / 50R42 LSW, SUPER TRACTION RADIAL
TRACK WIDTH - CENTER LINE OF TIRES	92"
TRANSMISSION	FOUR SPEED WITH TWO SPEED SHIFT ON THE GO
AUTO/MANUAL LEVELING	8° RIGHT AND 8° LEFT
AUTO LOAD CONTROL	ADJUSTABLE SET POINT
CAB	HEAT AND AIR CONDITIONING
HYDRAULIC DIFFERENTIAL LOCK	REAR AXLE - HYD. APPLIED
BRAKES	INDEPENDENT INBOARD REAR AXLE - HYD. APPLIED

ENGINE

MAKE & MODEL	CUMMINS QSG12 / TIER IVf
GROSS HORSEPOWER	350 HP @ 2100 RPM w/ POWER BULGE (385 HP)
DISPLACEMENT	11.8 LITER / 720 CU. IN.
FUEL TANK CAPACITY	150 GALLON
ELECTRICAL SYSTEM	24 VOLT (12V ACCESSORY)
BATTERIES - (2) 8D-MHD	2800 CCA RC 450
COLD STARTING AID	AIR INTAKE GRID HEATER

DIGGING WHEEL

DIGGING WHEEL DIAMETER	97 " INSIDE / 126" OUTSIDE
DIGGING WHEEL CONSTRUCTION	3/4" x 6" RIMS WITH 1/2" x 3" ATTACHING RING
DIGGING DEPTH RANGE	0 - 7' 3"
DIGGING WIDTH RANGE	20" - 40"
STANDARD CUTTING ARRANGEMENT	16" BUCKETS w/ CENTER CUTTERS (22" CUT)
SLOPER KIT	OPTIONAL
FRONT CENTER PIVOT	7° LEFT AND 7° RIGHT
GROUND CLEARANCE FOR TRANSPORT	BUCKETS - 36"
PIPE BOX	3" - 12" TILE LAYER, HYDRAULIC BEDDERS

CONVEYOR

LENGTH - 8' (STANDARD) 10' (OPTIONAL)
WIDTH - 36"
LEFT OR RIGHT DISCHARGE W/ 36" SHIFT

HYDRAULIC SYSTEM

150 GAL CAPACITY
CITGO TH FLUID OR EQUIVALENT
PRESSURE FILTRATION